



Department of Transportation
Federal Aviation Administration
Aircraft Certification Service
Washington, DC

TSO-C151b

**Date: December 17,
2002**

Technical Standard Order

Terrain Awareness and Warning System

Subject:

DISTRIBUTION: ZVS-326;A-W(IR)-3;A-X(FS)-3;A-X(CD)-4;
IR Form 8150-1 A-FFS-1,2,7,8(LTD);A-FAC-0(MAX);AFS-610 (2 cys)

1. PURPOSE. This technical standard order (TSO) tells persons seeking a TSO authorization or letter of design approval what minimum performance standards (MPS) their Terrain Awareness and Warning System (TAWS) equipment must first meet in order to obtain and be identified with the TSO-C151b Class A, B, or C marking.

NOTE: The MPS and test conditions for Class A and B are in appendices **1** and **3**. The Class C MPS and test conditions are located in appendix **4**. Class A and B TAWS equipment is required by Title 14 of the Code of Federal Regulations (14 CFR) parts 91, 135, and 121. Class C TAWS equipment is intended for voluntary installations on aircraft not covered by the TAWS requirements in 14 CFR parts 91, 135, and 121.

2. APPLICABILITY.

a. This TSO is effective for new applications submitted after the effective date of this TSO. All prior revisions to this TSO are no longer effective and, in general, applications will not be accepted after the effective date of this TSO. However, applications submitted against the previous versions of this TSO may be accepted up to six months after the effective date of this TSO, in cases where we know the applicant was working against the earlier MPS before the new change became effective.

b. Terrain Awareness and Warning Systems approved under a previous TSO authorization may continue to be manufactured under the provisions of their original approval, as specified in 14 CFR § 21.603(b). However, major design changes to TAWS equipment approved under previous versions of this TSO requires a new authorization under this TSO, per 14 CFR § 21.611(b).

3. REQUIREMENTS. New models of TAWS equipment that are to be so identified and that are manufactured on or after the effective date of this TSO must meet the MPS in appendices **1 through 4**.

a. Functionality. The standards of this TSO apply to equipment intended to provide the flight crews with both aural and visual alerts to aid in preventing an inadvertent controlled flight into terrain (CFIT) event.

b. Failure Condition Classification. A minimum level of reliability and integrity must be built into the TAWS computer for warning functions. Therefore, the presentation of hazardously misleading information (HMI), as defined in paragraph 2.8 of appendix 1, on the terrain display, or the unannounced loss of the terrain warning functions as a result of TAWS Computer failure is considered a major failure condition. A false terrain warning as a result of a TAWS computer failure is also considered a major failure condition. False sensor inputs (erroneous altitude, terrain data, airport data, etc) to the TAWS computer need not be considered for compliance to these failure condition classifications.

c. Functional Qualifications. The required performance must be demonstrated under the test conditions specified in appendices **1 through 4**.

d. Environmental Qualifications. The equipment must be subject to the test conditions specified in RTCA, Inc. Document No. RTCA/DO-160D, "Environmental Conditions and Test Procedures for Airborne Equipment," Change 4, dated July 29, 1997, or the most current revision. (Appendix 2 is reserved for modifications of, or additional requirements beyond the test procedures contained in RTCA/DO-160D.)

NOTE: FAA approved TAWS equipment certified to the FAA interim certification requirements that specified RTCA/DO-160C must be considered in compliance with TSO-C151b and must be entitled to a TSO-C151b authorization approval for the purpose of determining compliance with 14 CFR §§ 91.223, 121.354 and 135.154.

e. Software Qualifications. Software must be developed in accordance with sections 3 through 11 and Annex A of RTCA/DO-178B, "Software Consideration in Airborne Systems and Equipment Certification," dated December 1, 1992, or the most current revision. If the applicant proposes to use alternative methods, such as those in RTCA/DO-178B, section 12.3 or other alternative methods to qualify the software, the applicant should submit as early as possible to the FAA the proposed alternate method. This will allow for the FAA's timely review and acceptance of the proposed alternate method and for the timely resolution of any issues. Software implementing the functions defined in this TSO must be developed to Level C as defined in RTCA/DO-178B. Monitoring software required by appendix 1 of this TSO must be developed to Level C. Software in the TAWS other than the software implementing the function and monitoring requirements defined in the TSO, such as maintenance

software, should be developed to Level C also unless the applicant can demonstrate that the TSO functional software and monitoring software is protected from failure of the other software by means such as developed to the highest level commensurate with its functionality and its most severe failure condition categories as determined by a system safety assessment.

f. Fire Protection. All material used must be self-extinguishing except for small parts (such as knobs, fasteners, seals, grommets, and small electrical parts) that would not contribute significantly to the propagation of a fire.

g. Deviations. The FAA has provisions for using alternative or equivalent means of compliance to the criteria set forth in the MPS of this TSO. Applicants invoking these provisions must demonstrate that an equivalent level of safety is maintained and must apply for a deviation per 14 CFR § 21.609.

4. MARKING. Under 14 CFR § 21.607(d), articles manufactured under this TSO must be marked as follows:

a. At least one major component must be permanently and legibly marked with all of the information listed in 14 CFR § 21.607(d), except for the following: the option in 14 CFR § 21.607(d)(2), where the name, type and part number must be used in lieu of the optional model number; and the option in 14 CFR § 21.607(d)(3), where the date of manufacture must be used in lieu of the serial number.

b. In addition to the requirements of 14 CFR § 21.607(d), each separate component that is easily removable (without hand tools), each interchangeable element, and each separate sub-assembly of the article that the manufacturer determines may be interchangeable must be permanently and legibly marked with at least the name of the manufacturer, manufacturer's sub-assembly part number, and TSO number.

c. If the component includes a digital computer, the part number must include hardware and software identification, or a separate part number may be utilized for hardware and software. Either approach must include a means for showing the modification status. Note that similar software versions, which have been approved to different software levels, must be differentiated by part number.

5. DATA REQUIREMENTS.

a. Application Data. Under 14 CFR § 21.605(a)(2), the manufacturer must furnish the Manager, Aircraft Certification Office (ACO), Federal Aviation Administration (FAA), responsible for the manufacturer's facilities, one copy each of the following technical data to support the FAA design and production approval:

(1) Operating instructions and equipment limitations. The limitations must be sufficient to describe the operational capability of the equipment. In particular, operational or installation limitations resulting from specific deviations granted must be described in detail. The TAWS must contain processes by which the terrain database can be updated.

(2) Installation procedures and limitations. The limitations must be sufficient to ensure that the TAWS, when installed in accordance with the installation procedures, continues to meet the requirements of this TSO. The limitations must also be sufficient to identify any unique aspects of the installation. Finally, the limitations must include at least the following:

(i) A note with the following statement:

“The conditions and tests required for TSO approval of this article are minimum performance standards. It is the responsibility of those installing this article either on or within a specific type or class of aircraft to determine that the aircraft installation conditions are within the TSO standards. TSO articles must have separate approval for installation in an aircraft. The article may be installed only in compliance with 14 CFR part 43 or the applicable airworthiness requirements.”

(ii) When applicable, identify the appliance as an incomplete system or a multi-use system and describe any limitations and the functions that are intended to be provided by the appliance.

(3) Schematic drawings, as applicable to the installation procedures.

(4) Wiring drawings, as applicable to the installation procedures.

(5) Material and process specifications list.

(6) List of the components, by part number, that make up the TAWS system complying with the standards prescribed in this TSO. Manufacturers should include vendor part number cross-reference when applicable.

(7) Instructions in the form of a Component Maintenance Manual (CMM) containing information on periodic maintenance, calibration and repair, for the continued airworthiness of installed TAWS, including recommended inspection intervals and service life. Details of deviations granted, as noted in paragraph **5a(1)** of this TSO, may also be described in the CMM.

(8) Nameplate drawing providing the information required by paragraph **4** of this TSO.

(9) The quality control system description required by 14 CFR §§ 21.605(a)(3) and 21.143(a), including functional test specifications to be used to test each production article to ensure compliance with this TSO.

(10) Manufacturer’s TSO qualification test report, including appendix **2** modifications of, or additional requirements beyond the test procedures contained in RTCA/DO-160D.

(11) An environmental qualification form as described in RTCA/DO-160D or the most current revision for each component of the TAWS equipment.

(12) A list of all drawings and processes, including revision level, necessary to define the article's design. In the case of a minor change, any revisions to the drawing list need only be made available upon request.

(13) If the article includes software: Plan for Software Aspects of Certification (PSAC); Software Configuration Index; and Software Accomplishment Summary. The FAA recommends that the PSAC be submitted early in the software development process. Early submittal will allow timely resolution of issues such as partitioning and determination of software levels.

b. Manufacturer Data. In addition to the data to be furnished directly to the FAA, each manufacturer must have available the following technical data:

(1) The functional qualification specifications to be used to qualify each production article to ensure compliance with this TSO.

(2) Corrective maintenance procedures within 12 months after TSO authorization.

(3) Equipment calibration procedures.

(4) Material and process specifications.

(5) Schematic drawings.

(6) Wiring diagrams.

(7) The results of the environmental qualification tests conducted in accordance with RTCA/DO-160D, including appendix 2 modifications, or additional requirements beyond the test procedures contained in RTCA/DO-160D.

c. Furnished Data.

(1) One copy of the technical data and information specified in paragraphs **5a(1)** through **(6)** of this TSO and any other data or information necessary for the proper installation, certification, use, and continued airworthiness of the TAWS must accompany each article manufactured under this TSO.

(2) If the appliance accomplishes any additional functions beyond that described in paragraphs **3** and **3a** of this TSO, then a copy of the data and information specified in paragraphs **5a(11)** through **(13)** must also go to each person receiving for use one or more articles manufactured under this TSO.

6. AVAILABILITY OF REFERENCED DOCUMENTS.

a. Copies of RTCA Documents Nos. RTCA/DO-160D, "Environmental Conditions and Test Procedures for Airborne Equipment," dated July 29, 1997, RTCA/DO-161A, "Minimum Performance Standards - Airborne Ground Proximity Warning Equipment," dated May 27, 1976, RTCA/DO-200A/ EURCAE ED76, "Standards for Processing Aeronautical Data," dated September 18, 1998, and RTCA/DO-178B, "Software Considerations in Airborne Systems and Equipment Certification," dated

December 1, 1992, may be purchased from RTCA Inc., 1140 Connecticut Avenue, NW, Suite 1020, Washington, D.C. 20036.

b. 14 CFR part 21, Subpart O, Technical Standard Order Authorizations, may be purchased from the Superintendent of Documents, Government Printing Office, Washington,

DC 20402-9325. Copies may also be obtained from the Government Printing Office from their website at www.access.gpo.gov/ecfr/.

Carol MartineauDavid Hempe
Acting Manager, Aircraft Engineering Division
Aircraft Certification Service

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B**1.0 Introduction.**

1.1 Purpose. This standard provides the MPS for a Terrain Awareness and Warning System (TAWS).

1.2 Scope. This appendix sets forth the standard for two Classes of TAWS equipment. Class A equipment is required for certain 14 CFR part 121 operators and certain 14 CFR part 135 operators. Class B equipment is required for certain 14 CFR part 135 operators and certain 14 CFR part 91 operators. See Table 11-1 and the appropriate operating rules for specific details.

1.3 System Function and Overview. The system must provide the flight crew with sufficient information and alerting to detect a potentially hazardous terrain situation that would permit the flight crew to take effective action to prevent a controlled flight into terrain (CFIT) event. The basic TAWS functions for all TSO approved systems include the following:

- a.** A Forward Looking Terrain Avoidance (FLTA) function. The FLTA function looks ahead of the airplane along and below the airplane's lateral and vertical flight path and provides suitable alerts if a potential CFIT threat exists.
- b.** A Premature Descent Alert (PDA) function. The PDA function of the TAWS uses the airplane's current position and flight path information as determined from a suitable navigation source and airport database to determine if the airplane is hazardously below the normal (typically 3 degree) approach path for the nearest runway as defined by the alerting algorithm.
- c.** An appropriate visual and aural discrete signal for both caution and warning alerts.
- d.** Class A TAWS equipment must provide terrain information to be presented on a display system.
- e.** Class A TAWS equipment must provide indications of imminent contact with the ground for the following conditions as further defined in RTCA/DO-161A, Minimum Performance Standards - Airborne Ground Proximity Warning Equipment, dated May 27, 1976, and section 3.3 of this appendix. Deviations from RTCA/DO-161A are acceptable providing the nuisance alert rate is minimized while an equivalent level of safety for the following conditions is provided.
 - (1)** Excessive Rates of Descent
 - (2)** Excessive Closure Rate to Terrain.
 - (3)** Negative Climb Rate or Altitude Loss After Take-off
 - (4)** Flight Into Terrain When Not in Landing Configuration
 - (5)** Excessive Downward Deviation From an ILS Glideslope.

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

(6) Voice callout “Five Hundred” when the airplane descends to 500 feet above the terrain or nearest runway elevation

NOTE: Class A equipment will be entitled to a TSO-C92c authorization approval for the purpose of complying with the mandatory GPWS requirements in 14 CFR §§ 121.360 and 135.153, until such time that those rules are superceded by TAWS rules.

f. Class B equipment must provide indications of imminent contact with the ground during the following airplane operations as defined in section 3.4 of this appendix.

- (1)** Excessive Rates of Descent
- (2)** Negative Climb Rate or Altitude Loss After Takeoff
- (3)** A voice callout “Five Hundred” when the airplane descends to 500 feet above the nearest runway elevation.

1.4 Added Features. If the manufacturer elects to add features to the TAWS equipment, those features must at least meet the same qualification testing and software verification and validation requirements as provided under this TSO. Additional information such as “human-made” obstacles may be added as long as they do not adversely alter the terrain functions.

1.5 Other Technologies. Although this TSO envisions a TAWS based on the use of an onboard terrain and airport database, other technologies such as the use of radar are not excluded. Other concepts and technologies may be approved under this TSO using 14 CFR § 21.609, Approval for Deviation.

2.0 Definitions.

2.1 Alert. A visual, aural, or tactile stimulus presented to attract attention and convey information regarding system status or condition.

2.2 Aural Alert. A discrete sound, tone, or verbal statement used to annunciate a condition, situation, or event.

2.3 Caution Alert. An alert requiring immediate crew awareness. Subsequent corrective action will normally be necessary.

2.4 Controlled Flight Into Terrain (CFIT). An accident or incident in which an airplane, under the full control of the pilot, is flown into terrain, obstacles, or water.

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

2.5 Failure. The inability of the equipment or any sub-part of that equipment to perform within previously specified limits.

2.6 False Alert. An inappropriate alert that occurs as a result of a failure within the TAWS or when the design alerting thresholds of the TAWS are not exceeded.

2.7 Hazard. A hazard is a state or set of conditions that together with other conditions in the environment could lead to an accident.

2.8 Hazardously Misleading Information (HMI). An incorrect depiction of the terrain threat relative to the airplane during an alert condition (excluding source data).

2.9 Nuisance Alert. An inappropriate alert, occurring during normal safe procedures, that occurs as a result of a design performance limitation of TAWS.

2.10 Search Volume. A volume of airspace around the airplane's current and projected path that is used to define a TAWS alert condition.

2.11 Visual Alert. The use of projected or displayed information to present a condition, situation, or event.

2.12 Warning Alert. An alert for a detected terrain threat that requires immediate crew action.

3.0 Required TAWS Functions.

3.1 Class A and Class B Requirements for Forward Looking Terrain Avoidance (FLTA). The majority of CFIT accidents have occurred because the flight crews did not have adequate situational information regarding the terrain in the vicinity of the airplane and its projected flight path. Class A and Class B Equipment will be required to look ahead of the airplane, within their design search volume and provide timely alerts in the event terrain is predicted to penetrate the search volume. The FLTA function should be available during all airborne phases of flight including turning flight. The search volume consists of a computed look ahead distance, a lateral distance on both sides of the airplane's flight path, and a specified look down distance based upon the airplane's vertical flight path. This search volume should vary as a function of phase of flight, distance from runway, and the required obstacle clearance (ROC) in order to perform its intended function and to minimize nuisance alerts. The lateral search volume should expand as necessary to accommodate turning flight. The TAWS search volumes should consider the accuracy of the TAWS navigation source. The TAWS lateral search area should be less than the protected area defined by the United States Standard for Terminal Instrument Procedures (TERPS), FAA Handbook 8260.3B and ICAO PANOPS 8168, volume 2, to prevent nuisance alerts.

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

3.1.1 Reduced Required Terrain Clearance (RTC). Class A and Class B equipment must provide suitable alerts when the airplane is currently above the terrain in the airplane's projected flight path but the projected amount of terrain clearance is considered unsafe for the particular phase of flight. The required obstacle (terrain) clearance (ROC) as specified in TERPS and the Aeronautical Information Manual (AIM) have been used to define the minimum requirements for obstacle/terrain clearance (RTC) appropriate to the FLTA function. These requirements are specified in Table 3.1. The FLTA function must be tested to verify the alerting algorithms to meet the test conditions specified in appendix 3, Tables A, B, C, D, E, and F.

TABLE 3.1

TAWS REQUIRED TERRAIN CLEARANCE (RTC) BY PHASE OF FLIGHT			
Phase of Flight	TERPS (ROC)	TAWS (RTC) Level Flight	TAWS (RTC) Descending
Enroute	1000 Feet	700 Feet	500 Feet
Terminal (Intermediate Segment)	500 Feet	350 Feet	300 Feet
Approach	250 Feet	150 Feet	100 Feet
Departure (See Note 1)	48 Feet/NM	100 Feet	100 Feet

NOTE 1: During the Departure Phase of Flight, the FLTA function of Class A and B equipment must alert if the airplane is projected to be within 100 feet vertically of terrain. However, Class A and Class B equipment should not alert if the airplane is projected to be more than 400 feet above the terrain.

NOTE 2: As an alternate to the stepped down reduction from the terminal to approach phase in Table 3.1, a linear reduction of the RTC as the aircraft comes closer to the nearest runway is allowed, providing the requirements of Table 3.1 are met.

NOTE 3: During the visual segment of a normal instrument approach (typically about 1 NM from the runway threshold), the RTC should be defined/reduced to minimize nuisance alerts. Below a certain altitude or distance from the runway threshold, logic may be incorporated to inhibit the FLTA function. Typical operations below Minimum Descent Altitude (MDA), Decision Height (DH), or the Visual Descent Point (VDP) should not generate nuisance alerts.

NOTE 4: The specified RTC values are reduced slightly for descending flight conditions to accommodate the dynamic conditions and pilot response times.

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

3.1.2 Imminent Terrain Impact. Class A and Class B equipment must provide suitable alerts when the airplane is currently below the elevation of a terrain cell along the airplane's lateral projected flight path and, based upon the vertical projected flight path, the equipment predicts that the terrain clearance will be less than the value given in the RTC column of Table 3.1. See appendix 3 for test conditions that must be conducted (Table G).

3.1.3 FLTA Turning Flight. Class A and Class B equipment must provide suitable alerts for the functions specified in 3.1.1 and 3.1.2 above when the airplane is in turning flight.

3.2 Class A and Class B Equipment Requirements for Detection and Alerting for Premature Descent Along the Final Approach Segment. Class A and Class B equipment must provide a suitable alert when it determines that the airplane is significantly below the normal approach flight path to a runway. Approximately one third of all CFIT accidents occur during the final approach phase of flight, when the airplane is properly configured for landing and descending at a normal rate. For a variety of reasons, which include poor visibility, night time operations, loss of situational awareness, operating below minimums without adequate visual references and deviations from the published approach procedures, many airplanes have crashed into the ground short of the runway. A means to detect and alert the flight crew to this condition is an essential safety requirement of this TSO. There are numerous ways to accomplish the overall objectives of this requirement. Alerting criteria may be based upon height above runway elevation and distance to the runway. It may be based upon height above terrain and distance to runway or other suitable means. This TSO will not define the surfaces for which alerting is required. It will specify some general requirements for alerting and some cases when alerting is inappropriate. See appendix 3 Table H for test requirements.

- a.** The PDA function should be available for all types of instrument approaches. This includes both straight-in approaches and circling approaches. This includes approaches that are not aligned within 30 degrees of the runway heading.
- b.** The TAWS equipment should not generate PDA alerts for normal VFR operations in the airport area. Airplanes routinely operate at traffic pattern altitudes of 800 feet above field/runway elevation for traffic pattern operations within 5 NM of the airport.
- c.** Airplanes routinely operate in VFR conditions at 1000 feet AGL within 10-15 NM of the nearest airport and these operations should not generate alerts.

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

d. Airplanes routinely operate in the visual segment of a circling approach within 2 NM of the airport/runway of intended landing with 300 feet of obstacle clearance. Operations at circling minimums should not cause PDA alerts or FLTA alerts.

3.3 Class A Requirements for GPWS Alerting. In addition to the TAWS Forward Looking Terrain Avoidance and PDA functions, the equipment must provide the GPWS functions listed below in accordance with TSO-C92c. Some GPWS alerting thresholds may be adjusted or modified to be more compatible with the FLTA alerting functions and to minimize GPWS nuisance alerts. However, it is essential to retain the independent protective features provided by both the GPWS and FLTA functions. In each case, all the following situations must be covered. The failure of the TSO-C92c equipment functions, except for power supply failure, input sensor failure, or failure of other common portions of the equipment, must not cause a loss of the FLTA, PDA, or Terrain Display.

The functions described in TSO-C92c and the referenced document RTCA/DO-161A include:

- (1) Excessive Rates of Descent
- (2) Excessive Closure Rate to Terrain
- (3) Negative Climb Rate or Altitude Loss After Take-Off
- (4) Flight Into Terrain When Not in Landing Configuration
- (5) Excessive Downward Deviation From an ILS Glideslope

a. Flap Alerting Inhibition. A separate guarded control may be provided to inhibit GPWS alerts based on flaps being other than the landing configuration.

b. Speed. Airspeed or groundspeed must be included in the logic that determines basic GPWS alerting time for “Excessive Closure Rate to Terrain” and “Flight Into Terrain When Not in Landing Configuration” to allow maximum time for the flight crew to react and take corrective action.

c. Voice Callouts. Voice callouts of altitude above the terrain must be provided during nonprecision approaches per TSO-C92, but are recommended for all approaches. These advisories are normally, but are not limited to 500 feet above the terrain or the height above the nearest runway threshold elevation.

d. Barometric Altitude Rate. Class A and Class B equipment may compute Barometric Altitude Rate using an Instantaneous Vertical Speed Indicator (IVSI) or an inertial smoothed vertical speed indicator. An alternative means, with demonstrated equal or better accuracy, may be used in lieu of barometric altitude rate (accuracy specified in TSO-C10b, Altimeter, Pressure

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

Actuated, Sensitive Type, or later revisions) and/or altimeter altitude (accuracy specified in TSO-C67, Airborne Radar Altimeter Equipment - for air carrier aircraft, or later revisions) to meet the warning requirements described in RTCA/DO-161A. In addition, TSO-C106 for Air Data Computers may be used as an alternative means of compliance with this provision.

e. Sweep Tones “Whoop-Whoop”. If a two-tone sweep is used to comply with RTCA /DO-161A, paragraph 2.3, the complete cycle of two-tone sweeps plus annunciation may be extended from “1.4” to “2” seconds.

NOTE: Class A equipment will be entitled to a TSO-C92c authorization approval for the purpose of complying with the mandatory GPWS requirements in 14 CFR §§ 121.360 and 135.153 until such time that those rules are superceded by TAWS rules.

3.4 Class B Requirements for GPWS Alerting

a. Class B equipment must provide alerts for excessive descent rates. The alerting envelope of RTCA/DO-161A has been modified to accommodate a larger envelope for both caution and warning alerts. Height above Terrain may be determined by using the Terrain Data Base elevation and subtracting it from QNH barometric altitude (or equivalent). In addition, since the envelopes are not limited by a radio altitude measurement to a maximum of 2500 feet AGL, the envelopes are expanded to include higher vertical speeds. The equipment must meet either the requirements set forth in appendix 3, section 7.0 or that specified in DO-161A.

b. Class B equipment must provide alerts for “Negative Climb Rate After Takeoff or Missed Approach” or “Altitude Loss After Takeoff” as specified in RTCA/DO-161A. The alerting is identical to the alerting envelope in RTCA/DO-161A except that Height above Terrain is based upon Height above Runway threshold elevation instead of radio altitude.

c. Class B equipment must provide a voice callout “Five Hundred” during descents for landing. This feature is primarily intended to provide situational awareness to the flight crew when the airplane is being operated properly per normal procedures. During a normal approach, it is useful to provide the flight crew with a 500-foot voice callout referenced to the runway threshold elevation for the runway of intended landing. This feature also has an important CFIT protection function. In the event the airplane is operated unintentionally close to terrain when not

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

in the airport area or the area for which PDA protection is provided, a 500-foot voice callout referenced to Height above Terrain will alert the flight crew to a hazardous condition.

The equipment must meet the requirements specified in appendix 3, section 9.0.

NOTE 1: Class B equipment will not require a radio altimeter. Height above Terrain may be determined by subtracting the elevation of the current position terrain cell from the current barometric altitude (or equivalent).

NOTE 2: Class B equipment should compute the voice callout for five hundred feet based upon barometric height above runway elevation. The nearest runway elevation may be used for this purpose.

3.5 Class A Equipment Requirements for a Terrain Display. Class A equipment must be designed to interface with a Terrain Display, either color or monochromatic. Class A equipment for TAWS must be capable of providing the following terrain related information to a display system.

- a.** The terrain must be depicted relative to the airplane's position such that the pilot may estimate the relative bearing to the terrain of interest.
- b.** The terrain must be depicted relative to the airplane's position such that the pilot may estimate the distance to the terrain of interest.
- c.** The terrain depicted must be oriented to either the heading or track of the airplane. In addition, a North-up orientation may be added as a selectable format.
- d.** Variations in terrain elevation depicted relative to the airplane's elevation (above and below) must be visually distinct. Terrain that is more than 2000 feet below the airplane's elevation need not be depicted.
- e.** Terrain that generates alerts must be displayed in a manner to distinguish it from non-hazardous terrain, consistent with the caution and warning alert level.

3.6 Class B Equipment Requirements for a Terrain Display. Operators required to install Class B equipment are not required to include a Terrain Display. However, Class B TAWS

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

equipment must be capable of driving a terrain display function in the event the installer wants to include the terrain display function.

NOTE: This TSO does not include requirements for the display system/hardware.

4.0 Aural and Visual Alerts.

4.1 The TAWS is required to provide aural alerts and visual alerts for each of the functions described in section 3.0 of this appendix.

4.2 The required aural and visual alerts must initiate from the TAWS system simultaneously, except when suppression of aural alerts are necessary to protect pilots from nuisance aural alerting.

4.3 Each aural alert must identify the reason for the alert such as “too low terrain” and “Glideslope,” or other acceptable annunciation.

4.4 The system must remove the visual and aural alert once the situation has been resolved.

4.5 The system must be capable of accepting and processing airplane performance related data or airplane dynamic data and providing the capability to update aural and visual alerts at least once per second.

4.6 The aural and visual outputs as defined in Table 4-1 must be compatible with the standard cockpit displays and auditory systems.

4.7 The aural and visual alerts should be selectable to accommodate operational commonality among fleets of airplanes.

4.8 The visual display of alerting information must be immediately and continuously displayed until the situation is no longer valid.

4.9 As a minimum, the TAWS must be capable of providing aural alert messages described in Table 4 -

1. In addition to this minimum set, other voice alerts may be provided.

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

TABLE 4 – 1

Standard Set of Visual and Aural Alerts

Alert Condition

Caution

Warning

Reduced Required Terrain Clearance

Class A & Class B

Visual Alert

Amber text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

Minimum Selectable Voice Alerts:

“Caution, Terrain; Caution, Terrain” **and**

“Terrain Ahead; Terrain Ahead”**Visual Alert**

Red text message that is obvious, concise and must be consistent with the Aural message.

Aural Alert

Minimum Selectable Voice Alerts:

“Terrain, Terrain; Pull-Up, Pull- up” **and** “Terrain Ahead, Pull- up; Terrain Ahead, Pull-Up”

Imminent Impact with Terrain

Class A & Class B**Visual Alert**

Amber text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

Minimum Selectable Voice Alerts:

“Caution, Terrain; Caution, Terrain” **and**

“Terrain Ahead; Terrain Ahead”**Visual Alert**

Red text message that is obvious, concise and must be consistent with the Aural message.

Aural Alert

Minimum Selectable Voice Alerts:

“Terrain, Terrain; Pull-Up, Pull- up” **and**

“Terrain Ahead, Pull- up; Terrain Ahead, Pull-Up”

Premature Descent Alert (PDA)

Class A & Class B**Visual Alert**

Amber text message that is obvious, concise and must be consistent with the Aural message.

Aural Alert

“Too Low Terrain”**Visual Alert**

None Required

Aural Alert

None Required

Ground Proximity Envelope 1, 2 or 3
Excessive
Descent Rate

Class A & Class B**Visual Alert**

Amber text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

“Sink Rate”**Visual Alert**

Red text message that is obvious, concise and must be consistent with the Aural message.

Aural Alert

“Pull-Up”

Ground Proximity Excessive Closure Rate (Flaps not in Landing Configuration)

Class A**Visual Alert**

Amber text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

“Terrain-Terrain”**Visual Alert**

Red text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

“Pull-Up”

Ground Proximity Excessive Closure Rate (Landing Configuration)

Class A**Visual Alert**

Amber text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

“Terrain-Terrain”**Visual Alert**

None Required.

Aural Alert

“Pull-Up” – for gear up

None Required – for gear down

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

TABLE 4 – 1 (Continued)

Standard Set of Visual and Aural Alerts

Alert Condition **Caution** **Warning**

Ground Proximity

Altitude Loss after Take-off

Aural Alert

Amber text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

“Don’t Sink” and “Too Low-Terrain”**Visual Alert**

None Required.

Ground Proximity Envelope 1
(Not in Landing Configuration)

Class A**Visual Alert**

Amber text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

“Too Low Terrain” and “Too Low Gear”**Visual Alert**

None Required.

Ground Proximity Envelope 2
Insufficient Terrain Clearance
(Landing and Go-around configuration)

Class A**Visual Alert**

Amber text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

“Too Low Terrain” and “Too Low Flaps”**Visual Alert**

None Required.

Aural Alert

None Required

Ground Proximity
Envelope 3
Insufficient Terrain Clearance
(Take-off configuration)

Class A **Visual Alert**

Amber text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

“Too Low Terrain” **Visual Alert**

None Required.

Aural Alert

None Required

Ground Proximity Excessive Glide Slope Deviation

Class A **Visual Alert**

Amber text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

“Glide Slope” **Visual Alert**

None Required.

Aural Alert

None Required

Ground Proximity Voice Call Out

(See Note 1)

Class A & Class B **Visual Alert**

None Required

Aural Alert

“Five Hundred” **Visual Alert**

None Required.

Aural Alert

None Required

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

NOTE 1: The aural alert for Ground Proximity Voice Call Out is considered advisory.

NOTE 2: Visual alerts may be put on the terrain situational awareness display, if this fits with the overall human factors alerting scheme for the flight deck.

This does not eliminate the visual alert color requirements, even in the case of a monochromatic display. Typically in such a scenario adjacent colored annunciator lamps meet the alerting color requirements.

4.10 Prioritization

a. Class A Equipment. Class A Equipment must have an interactive capability with other external alerting systems so an alerting priority can be automatically executed for the purpose of not causing confusion or chaos on the flight deck during multiple alerts from different alerting systems. Typical alerting systems that may be interactive with TAWS include Predictive Windshear (PWS), Reactive Windshear (RWS), and possibly in the future Traffic Collision Avoidance System (TCAS). Table 4-2 includes an alert prioritization scheme. If the PWS, RWS and/or TCAS functions are provided within the TAWS, Table 4-2 also applies. The FAA will consider alert prioritization schemes other than the one included in Table 4-2.

b. Class B Equipment. Class B Equipment does not require prioritization with external systems such as TCAS, RWS, and PWS. If prioritization with those functions is provided, the prioritization scheme must be in accordance with the Table 4-2.

c. Class B Equipment. Class B equipment must establish an internal priority alerting system (scheme) for each of the functions. The priority scheme must ensure that more critical alerts override the presentation of any alert of lesser priority. Table 4-3 is the internal priority scheme of the system. Class B equipment need only consider the TAWS functions required for Class B equipment.

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

Table 4-2
ALERT PRIORITIZATION SCHEME

Priority	Description	Alert Level	Comments
1	Reactive Windshear Warning	W	
2	Sink Rate Pull-Up Warning	W	continuous
3	Excessive Closure Pull-Up Warning	W	continuous
4	RTC Terrain Warning	W	
5	V1 Callout	I	
6	Engine Fail Callout	W	
7	FLTA Pull-Up warning	W	continuous
8	PWS Warning	W	
9	RTC Terrain Caution	C	continuous
10	Minimums	I	
11	FLTA Caution	C	7 s period
12	Too Low Terrain	C	
13	PDA ("Too Low Terrain")	Caution	C
14	Altitude Callouts	I	
15	Too Low Gear	C	
16	Too Low Flaps	C	
17	Sink Rate	C	
18	Don't Sink	C	
19	Glideslope	C	3 s period
20	PWS Caution	C	
21	Approaching Minimums	I	
22	Bank Angle	C	
23	Reactive Windshear Caution	C	
Mode 6 a	TCAS RA ("Climb", "Descend", etc.)	W	continuous
Mode 6 a	TCAS TA ("Traffic, Traffic")	C	continuous

NOTE 1: These alerts can occur simultaneously with TAWS voice callout alerts.

NOTE 2: W = Warning, C = Caution, A = Advisory, I = Informational

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

Table 4-3

TAWS INTERNAL ALERT PRIORITIZATION SCHEME
Priority**Description**

1.	Sink Rate Pull-Up Warning
2.	Terrain Awareness Pull-Up warning
3.	Terrain Awareness Caution
4.	PDA ("Too Low Terrain") Caution
5.	Altitude Callouts "500"
6.	Sink Rate
7.	Don't Sink (Mode 3)

4.11 During ILS or other localizer-based approach operations, TAWS should not cause an alert for a terrain/obstacle located outside the TERPS protected airspace. Special design considerations may be necessary to address this issue.

NOTE 1: Non-GPS RNAV/FMC Systems that are used for the TAWS airplane horizontal airplane information may be "Localizer Updated" to remove cross track errors. In addition, the alerting envelope may be modified to account for the higher accuracy and closer obstacles associated with ILS conditions.

NOTE 2: GPS-based Systems that are used for the TAWS airplane horizontal airplane position information should be able to meet the minimum criteria found in appendix 1, section 5.0.

NOTE 3: The level off initiation height of 20 percent of the vertical speed was chosen (as a minimum standard for nuisance alarm-free operations) because it is similar to typical autopilot or flight director level off (altitude capture) algorithms whereas the technique of using 10 percent of the existing vertical speed as a level off initiation point is usually considered as a minimum appropriate only to manual operations of smaller general aviation airplanes. With high rates of descent, experienced pilots often use a manual technique of reducing the vertical speed by one half when reaching 1000 feet above/below the level off altitude. This technique will significantly reduce the likelihood of nuisance alerts. In the event that use of the 20 percent of vertical speed as a minimum standard for nuisance free operations is shown not to be compatible with the installed autopilot or flight director level off (altitude capture) algorithms, consideration should be given to setting the alert logic closer to the 10 percent vertical speed criteria to minimize nuisance alerts.

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

5.0 Airplane Horizontal Position Determination for Source Data.

5.1 Class A equipment. Class A equipment that uses the on-board airplane navigation system for horizontal position information for the TAWS and that meets TSO-C115 or follows AC90-45A for approved RNAV systems, TSO-C129a for GPS, TSO-C145 for WAAS, or that follows the recommendations in AC 20-130a or AC-138 are considered acceptable. See note below.

5.2 Class B equipment. Class B equipment will be required to interface with an approved GPS for horizontal position information as specified in 5.1. See note below.

NOTE: Experience with these systems to date and analysis support that, as position accuracy decreases, a larger area must be considered for alerts in order for the system to perform its intended function. As the area of consideration is expanded and position accuracy is decreased the system tends to become more prone to nuisance alerts. In order to keep the system nuisance free, the TAWS must be inhibited or its operation degraded to accommodate certain types of operations. Therefore designers should be aware that at the present time only systems that use position information which provides GPS accuracy will be considered to meet this TSO except for aircraft operated under 14 CFR part 121. Operations under 14 CFR part 121 provide factors that compensate for the decreased accuracy. These factors include type of operation, route structure analysis, flight crew training, route proving requirements, continued surveillance, and extensive operations into a limited number of airports.

5.3 Internal GPS Navigator Function. Class A and Class B equipment that use a GPS internal to the TAWS for horizontal position information and are capable of detecting a positional error that exceeds the appropriate alarm limit for the existing phase of flight in accordance with TSO - C129a/RTCA/DO-208, or equivalent are considered acceptable. When this alarm limit is activated, the GPS computed position is considered unsuitable for the TAWS function, and an indication should be provided to the flight crew that the TAWS functions that require GPS for operation are no longer available.

6.0 Class A and Class B Requirements for a Terrain and Airport Database.

6.1 Minimum Geographical Considerations. As a minimum, terrain and airport information must be provided for the expected areas of operation, airports and routes to be flown.

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

6.2 Development and Methodology. The manufacturer must present the development and methodology used to validate and verify the terrain and airport information. RTCA/DO-200A/EUROCAE ED 76, Standards for Processing Aeronautical Data, should be used as a guideline.

6.3 Resolution. Terrain and airport information must be of the accuracy and resolution suitable for the system to perform its intended function. Terrain data should be gridded at 30 arc seconds with 100 foot resolution within 30 nautical miles of all airports with runway lengths of 3500 feet or greater and whenever necessary (particularly in mountainous environments) 15 arc seconds with 100 foot resolution (or even 6 arc seconds) within 6 nautical miles of the closest runway. It is acceptable to have terrain data gridded in larger segments over oceanic and remote areas around the world.

NOTE: Class B equipment may require information relative to airports with runways less than 3500 feet whether public or private. Small airplane owners and operators, and small non-schedule part 135 operators probably will be the largest market for Class B equipment. Such operators frequently use airports of less than 3500 feet. Those TAWS manufacturers who desire to sell to this market must be willing to customize their terrain databases to include selected airports used by their customers.

6.4 Updates and Continued Airworthiness. The system must be capable of accepting updated terrain and airport information.

7.0 Class A and Class B Failure Indication. Class A and Class B equipment must include a failure monitor function that provides reliable indications of equipment condition during operation. It must monitor the equipment itself, input power, input signals, and aural and visual outputs. A means must be provided to inform the flight crew whenever the system has failed or can no longer perform the intended function.

8.0 Class A and Class B Requirements for Self-Test. Class A and Class B equipment must have a self-test function to verify system operation and integrity. It must monitor the equipment itself, input power, input signals, and aural and visual outputs. Failure of the system to successfully pass the self-test must be annunciated.

NOTE: Flight crew verification of the aural and visual outputs during a self-test is an acceptable method for monitoring aural and visual outputs.

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

9.0 Class A Equipment Requirements for a Terrain Awareness Inhibit for the FLTA function, the Premature Descent Alert function and Terrain Display.

9.1 Manual Inhibit. Class A equipment must have the capability, via a control switch to the flight crew, to inhibit only the FLTA function, the Premature Descent Alert function, and Terrain Display. This is required in the event of a navigational system failure or other failures that would adversely affect FLTA, the Premature Descent Alert function or the Terrain Display. The basic TAWS required functions must remain active when the inhibit function is utilized.

9.2 Automatic Inhibit. The capability of automatically inhibiting Class A functions within TAWS equipment is acceptable utilizing the conditions described in section 7.0. If auto inhibit capability is provided, the “inhibit status” must be annunciated to the flight crew.

10.0 Phase of Flight Definitions. The TAWS equipment search volumes and alerting thresholds should vary as necessary to be compatible with TERPS and other operational considerations. For that reason, a set of definitions is offered for Enroute, Terminal, Approach and Departure Phases of Flight. Other definitions for enroute, terminal and approach may be used by TAWS provided they are compatible with TERPS and standard instrument approach procedures and will comply with the test criteria specified in appendix 3.

10.1 Enroute Phase. The Enroute Phase exists anytime the airplane is more than 15 NM from the nearest airport or whenever the conditions for Terminal, Approach and Departure Phases are not met.

10.2 Terminal Phase. The Terminal Phase exists when the airplane is 15 NM or less from the nearest runway while the range to the nearest runway threshold is decreasing and the airplane is at or below (lower than) a straight line drawn between the two points specified in Table 10-1 relative to the nearest runway.

TABLE 10-1

HEIGHT ABOVE RUNWAY VERSUS DISTANCE TO RUNWAY

Distance to Runway	Height above Runway
15 NM	3500 Feet
5 NM	1900 Feet

APPENDIX 1. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASSES A AND B (continued)

10.3 Approach Phase. Distance to nearest runway threshold is equal to, or less than 5 NM; and height above the nearest runway threshold location and elevation is equal to, or less than 1900 feet; and distance to the nearest runway threshold is decreasing.

10.4 Departure Phase. The Departure Phase should be defined by some reliable parameter that initially determines that the airplane is on the ground upon initial power-up. If, for example, the equipment can determine that the airplane is “on the ground” by using some logic such as ground speed less than 35 knots and altitude within +/- 75 feet of field elevation or nearest runway elevation) and “airborne” by using some logic such as ground speed greater than 50 knots and altitude 100 feet greater than field elevation, then the equipment can reliably determine that it is in the “Departure Phase.” Other parameters to consider are climb state, and distance from departure runway. Once the airplane reaches 1500 feet above the departure runway, the Departure Phase is ended.

11.0 Class A and Class B Summary Requirements. A Summary Table of Requirements is provided in Table 11-1. This is provided only as convenience and general information. Official, regulatory requirements are contained in the Federal Aviation Regulations.

TABLE 11-1

CLASS A AND B SUMMARY REQUIREMENTS

TAWS
CLASS
OPERATING
RULEPAX
SEATS
(MIN)FLTAPDAGPWS
DO-161AFMS/RNAV
OR
GPSTERRAIN
DISPLAY
MANDATORYTERRAIN/
AIRPORT
DATABASE
A121See NoteYESYES1-6FMS OR GPSYESYES
A135>9YESYES1-6GPSYESYES
B1356-9YESYES1,3,6GPSNOYES
B91= or >6YESYES1,3,6GPSNOYES

NOTE: There is no seat threshold for 14 CFR part 121. All 14 CFR part 121 airplanes affected by the TAWS rules must install TAWS regardless of number of seats.

Appendix 2**TSO-C151b****APPENDIX 2. STANDARDS APPLICABLE TO ENVIRONMENTAL TEST PROCEDURES**

**RESERVED FOR MODIFICATIONS OF OR ADDITIONAL REQUIREMENTS
BEYOND THE TEST PROCEDURES CONTAINED IN RTCA DOCUMENT No.
(RTCA/DO)-160D.**

APPENDIX 3. TEST CONDITIONS

1.0 Forward looking Terrain Avoidance - Reduced Required Terrain Clearance (RTC) Test Conditions. This condition exists, when the airplane is currently above the terrain but the combination of current altitude, height above terrain, and projected flight path indicates that there is a significant reduction in the Required Terrain Clearance (RTC).

1.1 Phase of Flight Definitions. For the following test conditions, refer to appendix 1, paragraph 10.0 for an expanded discussion on the definitions of the phases of flight.

1.2 Enroute Descent Requirement. A terrain alert must be provided in time so as to assure that the airplane can level off (L/O) with a minimum of 500 feet altitude clearance over the terrain/obstacle when descending toward the terrain/obstacle at any speed within the operational flight envelope of the airplane. The test conditions assume a descent along a flight path that has terrain that is 1000 feet below the expected level off altitude. If the pilot initiates the level off at the proper altitude, no TAWS alert would be expected. However, if the pilot is distracted or otherwise delays the level off, a TAWS alert is required to permit the pilot to recover to level flight in a safe manner.

a. See Table A. Column A represents the test condition. Columns B, C, and D are for information purposes only. Column E represents the Minimum Altitude for which TAWS alerts must be posted to perform their intended function. Column F represents the Maximum altitude for which TAWS alerts may be provided in order to meet the nuisance alert criteria. See appendix 3, section 4.0.

b. For each of the Descent rates specified below, recovery to level flight at or above 500 feet terrain clearance is required.

c. Test Conditions for 1.2:

Assumed Pilot response time:	3.0 seconds minimum
Assumed constant G pull-up:	0.25 g's
Minimum Allowed Terrain Clearance:	500 feet AGL
Descent rates:	1000, 2000, 4000, and 6000 fpm
<u>Assumed Pilot Task for Column F: Level off at 1000 feet above the terrain per TERPS Required Obstacle Clearance (ROC).</u>	

NOTE 1: The actual values for the airplane altitude, distance and time from the terrain cell when caution and warning alerts are posted and the minimum terrain clearance altitude must be recorded.

NOTE 2: Enroute operations are considered to exist beyond 15nm from the departure runway until 15 NM from the destination airport. Use of the nearest

APPENDIX 3. TEST CONDITIONS (continued)

runway logic is permissible provided suitable logic is incorporated to ensure that the transitions to the terminal logic will typically occur only when the airplane is in terminal airspace.

NOTE 3: The values shown in column E may be reduced by 100 feet (to permit a level off to occur at 400 feet above the obstacle) provided that it can be demonstrated that the basic TAWS Mode 1 alert (sink rate) is issued at, or above, the altitude specified in column E for typical terrain topographies.

NOTE 4: Class B Equipment Considerations. The values shown in Column F are appropriate for Autopilot or Flight Director operations with an Altitude Capture function typical of many 14 CFR part 25 certificated airplanes (Large Airplanes). The values are based upon 20 percent of the airplanes vertical velocity. If TAWS is installed on an airplane without such an Autopilot or Flight Director function, consideration should be given to computing the alerts based upon 10 percent of the vertical velocity which is more appropriate to manual flight and small general aviation airplane operations.

TABLE A

Enroute Descent Alerting Criteria
ABCDEF

VERT	
SPEED	
(FPM)ALT LOST	
WITH 3 SEC	
PILOT	
DELAYALT	
REQ'D TO	
L/O WITH	
0.25GTOTAL ALT	
LOST DUE TO	
RECOVERY	
MANEUVERMINIMUM	
TAWS WARNINGALERT HEIGHT	
(ABOVE	
TERRAIN)MAXIMUM	
CAUTION	
ALERT HEIGHT	
(ABOVE TERRAIN)	
1000501767567 1200	
200010069169669 1400	
4000200278478978 1800	

1.3 Enroute Level Flight Requirement. During level flight operations (vertical speed is +/- 500 feet per minute), a terrain alert should be posted when the airplane is within 700 feet of the terrain and is predicted to be equal to or less than 700 feet within the prescribed alerting time or distance. See Table B for Test Criteria.

NOTE 1: The actual values for the airplane altitude, distance and time from the terrain cell when caution and warning alerts are posted must be recorded.

APPENDIX 3. TEST CONDITIONS (continued)

TABLE B

Enroute Level Flight Alerting Criteria	
GROUND SPEED	
(KT)	HEIGHT OF TERRAIN CELL (MSL)
	TEST RUN
	ALTITUDE
	(MSL) ALERT
	CRITERIA
200	50006000 NO ALERT
250	50005800 NO ALERT
300	50005800 NO ALERT
200	50005700 (+0/-100) MUST ALERT
250	50005700 (+0/-100) MUST ALERT
300	50005700 (+0/-100) MUST ALERT
400	50005700 (+0/-100) MUST ALERT
500	50005700 (+0/-100) MUST ALERT

1.4 Terminal Area (Intermediate Segment) Descent Requirement. A terrain alert must be provided in time so as to assure that the airplane can level off (L/O) with a minimum of 300 feet altitude clearance over the terrain/obstacle when descending toward the terrain/obstacle at any speed within the operational flight envelope of the airplane. The test conditions assume a descent along a flight path that has terrain that is 500 feet below the expected level off altitude. If the pilot initiates the level off at the proper altitude, no TAWS alert would be expected. However, if the pilot is distracted or otherwise delays the level off, a TAWS alert is required to permit the pilot to recover to level flight in a safe manner.

a. See Table C: Column A represents the test condition. Columns B, C, and D are for information purposes only. Column E represents the Minimum Altitude for which TAWS alerts must be posted to perform their intended function. Column F represents the Maximum altitude for which TAWS alerts may be provided in order to meet the nuisance alert criteria. See appendix 3, section 4.0.

b. For each of the Descent rates specified below, recovery to level flight at or above 300 feet terrain clearance is required.

c. Test Conditions for 1.4:

Assumed Pilot response time: 1.0 second minimum

Assumed constant G pull-up: 0.25 g's

Minimum Allowed Terrain Clearance: 300 feet AGL

Descent rates: 1000, 2000, and 3000 fpm

Assumed Pilot Task for Column F: Level off at 500 feet above the terrain per TERPS Required Obstacle Clearance (ROC).

APPENDIX 3. TEST CONDITIONS (continued)

NOTE 1: The actual values for the airplane altitude, distance and time from the terrain cell when caution and warning alerts are posted and the minimum terrain clearance altitude must be recorded.

NOTE 2: For Class B Equipment Considerations. The values shown in Column F are appropriate for Autopilot or Flight Director operations with an Altitude Capture function typical of many 14 CFR part 25 certificated airplanes (Large Airplanes). The values are based upon 20 percent of the airplanes vertical velocity. If TAWS is installed on an airplane without such an Autopilot or Flight Director function, consideration should be given to computing the alerts upon 10 percent of the vertical velocity which is more appropriate to manual flight and small general aviation airplane operations.

TABLE C

Terminal Descent Area Alerting Criteria
ABCDEF

VERT	
SPEED	
(FPM)ALT LOST	
WITH 1 SEC	
PILOT	
DELAYALT	
REQ'D TO	
L/O WITH	
0.25GTOTAL ALT	
LOST DUE TO	
RECOVERY	
MANEUVERMINIMUM	
TAWS WARNING	
ALERT HEIGHT	
(ABOVE	
TERRAIN)MAXIMUM	
TAWS	
CAUTION ALERT HEIGHT	
(ABOVE TERRAIN)	
1000171734334700	
20003369102402900	
3000501562065061100	

1.5 Terminal Area (Intermediate Segment) Level Flight Requirement. During level flight operations (vertical speed less than +/-500 feet per minute), a terrain alert should be posted when the

airplane is less than 350 above the terrain and is predicted to be within less than 350 feet within the prescribed alerting time or distance. See Table **D** for Test Criteria.

NOTE 1: The actual values for the airplane altitude, distance and time from the terrain cell when caution and warning alerts are posted must be recorded.

APPENDIX 3. TEST CONDITIONS (continued)

TABLE D

Terminal Area Level Flight Alerting Criteria	
GROUND SPEED	
(KT)HEIGHT OF TERRAIN	
CELL (MSL)TEST RUN ALTITUDE	
(MSL)ALERT	
CRITERIA:	
15010001500	NO ALERT
20010001500	NO ALERT
25010001500	NO ALERT
10010001350	MUST ALERT
15010001350	MUST ALERT
20010001350	MUST ALERT
25010001350	MUST ALERT

1.6 Final Approach Segment Descent Requirement. A terrain alert must be provided in time to assure that the airplane can level off (L/O) with a minimum of 100 feet altitude clearance over the terrain/obstacle when descending toward the terrain/obstacle at any speed within the operational flight envelope of the airplane.

- a. See Table E. Column A represents the test condition. Columns B, C, and D are for information purposes only. Column E represents the Minimum Altitude for which TAWS alerts must be posted to perform their intended function. Column F represents the Maximum altitude for which TAWS alerts may be provided in order to meet the nuisance alert criteria. See appendix 3, section 4.0.
- b. For each of the Descent rates specified below, recovery to level flight at or above 100 feet terrain clearance is required.

c. Test Conditions for 1.6:

Assumed Pilot response time:	1.0 seconds minimum
Assumed constant G pull-up:	0.25 g's
Minimum Allowed Terrain Clearance:	100 feet AGL
Descent rates:	500, 750, 1000, and 1500 fpm
<u>Assumed Pilot Task for Column F: Level off at 250 feet above the terrain per TERPS Required Obstacle Clearance (ROC).</u>	

NOTE 1: The actual values for the airplane altitude, distance and time from the terrain cell when caution and warning alerts are posted and the minimum terrain clearance altitude must be recorded.

APPENDIX 3. TEST CONDITIONS (continued)

NOTE 2: For Class B equipment Considerations. The values shown in Column F are appropriate for Autopilot or Flight Director operations with an Altitude Capture function typical of many 14 CFR part 25 certificated airplanes (Large Airplanes). The values are based upon 20 percent of the airplanes vertical velocity. If TAWS is installed on an airplane without such an Autopilot or Flight Director function, consideration should be given to computing the alerts based upon 10 percent of the vertical velocity which is more appropriate to manual flight and small general aviation airplane operations.

TABLE E

ABCDEF

VERT					
SPEED					
(FPM)ALT LOST					
WITH 1 SEC					
PILOT					
DELAYALT					
REQ'D TO					
L/O WITH					
0.25GTOTAL ALT					
LOST DUE TO					
RECOVERY					
MANEUVERMINIMUM					
TAWS WARNING					
ALERT HEIGHT					
(ABOVE					
TERRAIN)MAXIMUM					
TAWS					
CAUTION ALERT HEIGHT					
(ABOVE TERRAIN)					
5008412112350					
750121022122400					
1000171835135450					
1500253964164550					

APPENDIX 3. TEST CONDITIONS (continued)

1.7 Final Approach Level Flight Requirement. During level flight operations at the Minimum Descent Altitude (MDA), a terrain alert should be posted when the airplane is within 150 feet of the terrain and is predicted to be within less than 150 feet within the prescribed alerting time or distance. See Table F for test criteria.

NOTE 1: The actual values for the airplane altitude, distance and time from the terrain cell when caution and warning alerts are posted must be recorded.

TABLE F

Final Approach Level Flight Alerting Criteria:

GROUND	
SPEED	
(KT)	HEIGHT OF
TERRAIN	
CELL (MSL)	DISTANCE
TERRAIN	
FROM RWY (NM)	TEST RUN
ALTI-TUDE	
(MSL)	ALERT
CRITERIA	
1204002.0650	NO ALERT
1404002.0650	NO ALERT
1604002.0650	NO ALERT
1204002.0600	MAY ALERT
1404002.0600	MAY ALERT
1604002.0600	MAY ALERT
1004002.0550	MUST ALERT
1204002.0550	MUST ALERT
1404002.0550	MUST ALERT
1604002.0550	MUST ALERT

APPENDIX 3. TEST CONDITIONS (continued)

2.0 Forward Looking Terrain Avoidance Imminent Terrain Impact Test Conditions. The following test conditions must be conducted to evaluate level flight performance during all phases of flight:

NOTE 1: The actual values for the airplane altitude, distance and time from the terrain cell when caution and warning alerts are posted must be recorded.

NOTE 2: Based upon a one second pilot delay and a 0.25 g incremental pull to constant 6.0 degree climb gradient, compute and record the airplane altitude at the terrain cell, the positive (or negative) clearance altitude, and the airplane position and time (after the alert), when the alert envelope is cleared.

2.1 Test Criteria. For each of the test cases below, a positive clearance of the terrain cell of interest is required.

2.2 Additional Test Criteria. Repeat each of the test cases below with the altitude error (-100 feet or -200 feet). A positive clearance of the terrain cell of interest is required.

TABLE G

Imminent Terrain Impact Alerting Criteria
GROUND
SPEED
(KT)HEIGHT OF
TERRAIN
CELL (MSL)DISTANCE
TERRAIN
FROM RWY (NM)TEST RUN
ALTITUDE
(MSL)ALERT
CRITERIA
20010000309000MUST ALERT
25010000309000MUST ALERT
30010000309000MUST ALERT
40010000308000MUST ALERT
50010000308000MUST ALERT
1502000101500MUST ALERT
2002000101500MUST ALERT
2502000101500MUST ALERT
1006005500MUST ALERT
1206005500MUST ALERT
1406005500MUST ALERT
1006004200MUST ALERT

1206004200MUST ALERT
1406004200MUST ALERT
1606004200MUST ALERT
1606005500MUST ALERT

APPENDIX 3. TEST CONDITIONS (continued)

3.0 Premature Descent Alert Test Conditions. The purpose of this test is to verify that the pilot will be alerted to a “low altitude condition” at an altitude that is defined by the specific design PDA Alert surface. This TSO will not define specific pass/fail criteria since, as stated in paragraph 3.2 of appendix 1, it does not define the surfaces for which alerting is required. The applicant must provide its proposed pass/fail criteria along with the proposed recovery procedures for the specific alerting criteria proposed by the applicant. In developing its test plan, the applicant should refer to paragraph 3.2 of appendix 1 that contain some general requirements for alerting and some cases when alerting is inappropriate. The applicant also may want to consider the recovery procedures specified in sections 1.2, 1.4, and 1.6 of paragraph 1 of appendix 3. The following test conditions must be conducted to evaluate PDA performance.

3.1 Test Conditions for 3.0 Premature Descent Alerts.

Descent rates: 750, 1500, 2000, 3000 FPM

Assumed Runway Elevation: Sea Level, Level Terrain

NOTE: For each test condition listed in Table H, compute and record the PDA alert altitude and the recovery altitude to level flight.

TABLE H

Premature Descent Alerting Criteria

GROUND	
SPEED	
(KT)VERT.	
SPEED	
(FPM)DISTANCE	
FROM RWY	
THRESHOLD	
(Touchdown)	
(NM)PDA	
ALERT HEIGHT	
(MSL)RECOVERY	
ALTITUDE	
(MSL)	
8075015	
100150015	
12075015	
140150015	
16075015	
200150015	
250200015	
8075012	
100150012	

12075012
140150012
16075012
807504

APPENDIX 3. TEST CONDITIONS (continued)

TABLE H (continued)

Premature Descent Alerting Criteria

GROUND	
SPEED	
(KT)VERT.	
SPEED	
(FPM)DISTANCE	
FROM RWY	
THRESHOLD	
(Touchdown)	
(NM)PDA	
ALERT HEIGHT	
(MSL)RECOVERY	
ALTITUDE	
(MSL)	
10015004	
1207504	
14015004	
807502	
10015002	
1207502	
14015002	

4.0 Nuisance Alert Test Conditions - General. The following test conditions must be conducted to evaluate TAWS performance during all phases of flight. The following general criteria apply:

4.1 4000 FPM. It must be possible to descend at 4000 FPM in the enroute airspace and level off 1000 feet above the terrain using a normal level off procedure (leading the level off by 20 percent of the vertical speed) without a caution or warning alert. See Table A.

4.2 2000 FPM. It must be possible to descend at 2000 FPM in the Terminal area and level off 500 feet above the terrain using the normal level off procedure described in 4.1 above, without a caution or warning alert. See Table C.

4.3 1000 FPM. It must be possible to descend at 1000 FPM in the Final Approach Segment and level off at the Minimum Descent Altitude (MDA) using the normal level off procedure described in 4.1 above, without a caution or warning alert. See Table E.

5.0 Nuisance Test Conditions for Horizontal and Vertical Flight Technical Errors. It must be shown, by analysis, simulation or flight testing, that the system will not produce nuisance alerts when

the airplane is conducting normal flight operations in accordance with published instrument approach procedure. This assumes the normal range in variation of input parameters.

APPENDIX 3. TEST CONDITIONS (continued)

5.1 Test Cases. As a minimum, the following cases (1-9) must be tested twice; one set of runs will be conducted with no lateral or vertical errors while another set of runs will be conducted with both lateral and vertical Flight Technical Errors (FTE). A lateral FTE of 0.3 NM and a vertical FTE of -100 feet (aircraft is closer to terrain) up to the FAF and a lateral FTE of 0.3 NM and a vertical FTE of -50 feet from the FAF to the Missed Approach Point (MAP) must be simulated. For all listed VOR, VOR/DME and Localizer based approaches, from the FAF to the MAP the airplane will descend at 1000 FPM until reaching either MDA (run #1) or MDA-50 feet (run #2). The airplane will then level off and fly level until reaching the MAP. Localizer updating of lateral position errors (if provided) may be simulated.

TABLE I

Nuisance Alert Test Conditions for Horizontal and
Vertical Flight Technical Errors

Case	Location	Operation
1	Quito, Ecuador	VOR ‘QIT’-ILS Rwy 35
2	Katmandu, Nepal	VOR-DME Rwy 2
3	Windsor Locks, CT	VOR Rwy 15
4	Calvi, France	LOC DME Rwy 18 / Circle
5	Tegucigalpa, Honduras	VOR DME Rwy 1 / Circle
6	Eagle, CO	LOC DME-C
7	Monterey, CA	LOC DME Rwy 28L
8	Juneau, AK	LDA-1 Rwy 8
9	Chambery, France	ILS Rwy 18

6.0 Test Conditions Using Known Accident Cases. The aircraft configuration and flight trajectory for each case may be obtained from the Operations Assessment Division, DTS-43, Volpe National Transportation Systems Center, Cambridge, Massachusetts or at the FAA web page at the following address: <http://www.faa.gov/avr/air/airhome.htm> or <http://www.faa.gov> and then select “Regulation and Certification”, select “Aircraft Certification”.

APPENDIX 3. TEST CONDITIONS (continued)

6.1 Test Report. The test report should include as many of the following parameters use to recreate the events. They are (1) latitude; (2) longitude; (3) altitude; (4) time from terrain at caution and warning alerts; (5) distance from terrain at caution and warning alerts; (6) ground speed; (7) true track; (8) true heading; (9) radio altitude; (height above terrain) (10) gear position; and (11) flap position.

6.2 Computation and Recording. In addition to the above when the warning is posted, for each test case, based upon a one second pilot delay and a 0.25 g incremental pull to a constant 6.0 degree climb gradient, do the following. Compute and record the airplane altitude at the terrain cell, the positive (or negative) clearance altitude, and the airplane position and time (after the alert), when the alert envelope is cleared.

NOTE: The terrain cell of interest is the one associated with the accident and not necessarily the terrain cell that caused the warning.

6.3 Test Criteria. In each of the test cases below, it must be necessary to demonstrate that the airplane profile clears the terrain cell of interest.

TABLE J

Known Accident Cases				
LOCATION	IATA			
CODE	DATE	AIRCRAFT	REGISTRATION	NUMBER
		La Paz, Bolivia	1/185N	819EA
		Flat Rock, NC	8/23/85N	600CM
		Windsor, MA	12/10/86N	65TD
		Eagle, CO	3/27/87N	31SK
Tegucigalpa, Honduras			10/21/89N	88705
		Halawa Point, HI	10/28/89N	707PV
		San Diego, CA	3/16/91N	831LC
		Rome, GA	12/11/91N	25BR
		Gabriels, NY	1/3/92N	55000
		Alamogordo, NM	6/24/92N	108SC
		E. Granby, CT	11/12/95N	566AA
		Buga, Columbia	12/20/95N	651AA
		Nimitz Hill, Guam	8/6/97H	7468

APPENDIX 3. TEST CONDITIONS (continued)

7.0 Class B Equipment Test Requirements for Excessive Descent Rate. Use the following performance envelopes down to a “Height above Terrain” value of 100 feet. Instead of using Height of Terrain as determined by a radio altimeter, determine “Height above Terrain” as determined by subtracting the Terrain Elevation (from the Terrain Data Base) from the current QNH barometric altitude (or equivalent). The curve represents the minimum heights at which alerting must occur.

NOTE: Class B equipment may be designed to meet the requirements of RTCA/DO-161A for Excessive Descent Rate in lieu of the requirements of 7.0

8.0 Class B Equipment Test Requirements for Negative Climb Rate or Altitude Loss After Takeoff. Use the existing performance envelopes specified in RTCA/DO-161A based upon a “Height above Runway” using barometric altitude (or equivalent) and runway elevation in lieu of radio altimeter inputs.

9.0 Class B Equipment Test Requirements for the Altitude Callouts. Instead of using Height of Terrain as determined by a radio altimeter, determine Height above runway as determined by subtracting the Runway Elevation (from the Airport Data Base) from the current barometric altitude (or equivalent). When the Height above Terrain value first reaches 500 feet, a single voice alert (“Five Hundred”) or equivalent must be provided.

Appendix 4

TSO-C151b

9

Page

APPENDIX 4. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASS C

1.0 Introduction.

1.1 This appendix describes modifications to this TSO for General Aviation (GA) category of aircraft not required to have TAWS equipment installed. Class C equipment is intended for small GA airplanes that are not required to install Class B equipment.

1.2 This appendix contains only modifications to existing requirements in this TSO. It is intended that Class C meet all Class B requirements that are not modified or addressed here. The paragraph numbers below relate directly to the paragraphs in appendices 1 and 3.

2.0 CLASS C.

Class C TAWS equipment must meet all the requirements of a Class B TAWS with the small aircraft modifications described herein. If the equipment is designed only to function as Class C, per these modifications, it should be appropriately marked as Class C so that it can be uniquely distinguished from the Class A and B TAWS required by 14 CFR parts 91, 135, and 121.

Modifications to Appendix 1.

Minimum performance Standards, MPS

1.1 Phase of Flight Definitions. For appendix 4, the terms “takeoff,” “cruise,” and “landing” are used instead of “departure,” “enroute,” and “approach” because they are more suitable to the GA environment.

Takeoff—positive ROC, inside traffic area, distance to nearest runway threshold is increasing, and airplane is below 1,000 feet.

Cruise—anytime the airplane is outside the airport traffic control area.

Landing—inside traffic area and distance to nearest runway threshold is decreasing, and airplane is below 1,000 feet.

1.2 Altitude Accuracy. A means must be provided to compute an actual MSL aircraft altitude value that is immune to temperature errors and manual correction mis-sets that would otherwise prevent the TAWS from performing its intended function. If the TAWS includes a terrain display output, this reference altitude value used for the TAWS alerts should also be output for display. Since the altitude value is necessarily based upon GPS derived MSL altitude, which is required for horizontal position in all class B & C TAWS, the displayed value must be labeled MSL/G or MSL-G, or other obvious acronym that relates to the pilot that altitude is GPS derived MSL altitude. .

APPENDIX 4. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASS C (continued)

1.3 (f)(3) System Function and Overview. This data is pilot selectable for both “altitude” and “inhibit.”

3.1.1 Reduced Required Terrain Clearance (RTC). The required terrain clearance in the Altered Table 3.1 applies to small aircraft flying visually, and the TERPS criteria need not apply to TAWS. Thus, ROC numbers more appropriate to low level visual flight have been chosen.

Alternate Table 3.1 is shown below.

TABLE 3.1

TAWS REQUIRED TERRAIN CLEARANCE (RTC) BY PHASE OF FLIGHT

Phase of Flight	Small Aircraft ROC	TAWS (RTC)	TAWS (RTC)
		Level Flight	Descending
Cruise	500 Feet	250 Feet	200 Feet
Takeoff	48 Feet/NM	100 Feet	100 Feet
Landing (See Note 1)	250 Feet	150 Feet	100 Feet

Note 1: During the Takeoff Phase of Flight, the FLTA function must alert if the aircraft is projected to be within 100 feet vertically of terrain. However, the equipment should not alert if the aircraft is projected to be more than 250 feet above the terrain.

3.3.c Voice Callouts. This data is pilot selectable for both “altitude” and “inhibit.”

APPENDIX 4. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASS C (continued)

4.0 Aural and Visual Alerts

TABLE 4 – 1
Standard Set of Visual and Aural Alerts

Alert Condition
Caution
Warning
Terrain Awareness Reduced Required Terrain Clearance

Visual Alert

Amber text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

Minimum Selectable Voice Alert:

“Caution, Terrain; Caution, Terrain”**Visual Alert**

Red text message that is obvious, concise and must be consistent with the Aural message.

Aural Alert

Minimum Selectable Voice Alert:

“Terrain; Terrain”

Terrain Awareness Imminent Impact with Terrain

Visual Alert

Amber text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

Minimum Selectable Voice Alert:

“Caution, Terrain; Caution, Terrain”**Visual Alert**

Red text message that is obvious, concise and must be consistent with the Aural message.

Aural Alert

Minimum Selectable Voice Alert:

“Terrain; Terrain”

Terrain Awareness Premature Descent Alert (PDA)

Visual Alert

Amber text message that is obvious, concise and must be consistent with the Aural message.

Aural Alert

“Too Low; Too Low”**Visual Alert**

None Required

Aural Alert

None Required

Ground Proximity Excessive
Descent Rate

Visual Alert

Amber text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

“Sink Rate”**Visual Alert**

Red text message that is obvious, concise and must be consistent with the Aural message.

Aural Alert

“Pull-Up”

Ground Proximity Altitude Loss after Take-off

Visual Alert

Amber text message that is obvious, concise, and must be consistent with the Aural message.

Aural Alert

“Don’t Sink”**Visual Alert**

None Required.

Aural Alert

None Required.

Ground Proximity Voice Call Out
(See Note 1)

Visual Alert

None Required

Aural Alert

“Five Hundred” or selected altitude**Visual Alert**

None Required.

Aural Alert

None Required

APPENDIX 4. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASS C (continued)

NOTE 1: The aural alert for Ground Proximity Voice Call Out is considered advisory.

NOTE 2: Visual alerts may be put on the terrain situational awareness display, if this fits with the overall human factors alerting scheme for the flight deck. This does not eliminate the visual alert color requirements, even in the case of a monochromatic display. Typically in such a scenario, adjacent colored enunciator lamps meet the alerting color requirements. Audio alerts are still required regardless of terrain display visual alerts.

Modifications to Appendix 3, Test Conditions.

NOTE 1: Paragraph 1.1 of the TSO is not applicable; for small aircraft only three phases of flight are considered, take-off, cruise, and final approach to landing

NOTE 2: Paragraph 1.2 of the TSO is changed to specify altitude levels, test speeds and pull-ups more appropriate for small aircraft:

1.2 Cruise Descent Requirements. A terrain alert must be provided in time so as to assure that the airplane can level off (L/O) with a minimum of 200 feet altitude clearance over the terrain/obstacle when descending toward the terrain/obstacle at any speed within the operational flight envelope of the airplane. The test conditions assume a descent along a flight path that has terrain that is 500 feet below the expected level off altitude. If the pilot initiates the level off at the proper altitude, no TAWS alert would be expected. However, if the pilot is distracted or otherwise delays the level off, a TAWS alert is required to permit the pilot to recover to level flight in a safe manner.

- a.** See Table A. Column A represents the test condition. Columns B, C, and D are for information purposes only. Column E represents the Minimum Altitude for which TAWS alerts must be posted to perform their intended function. Column F represents the Maximum altitude for which TAWS alerts may be provided in order to meet the nuisance alert criteria. See appendix 3, section 4.0
- b.** For each of the Descent rates specified below, recovery to level flight at or above 200 feet terrain clearance is required.

APPENDIX 4. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASS C (continued)

c. Test Conditions for 1.2:

Assumed Pilot response time:	3.0 seconds minimum
Assumed constant G pull-up:	1.0 g
Minimum Allowed Terrain Clearance:	200 feet AGL
Descent rates:	500, 1000, and 2000 fpm

Assumed Pilot Task for Column F: Level off at 500 feet above the terrain per Appendix 4 Table 3-1 Required Obstacle Clearance (ROC).

NOTE 1: The actual values for the airplane altitude, distance and time from the terrain cell when caution and warning alerts are posted and the minimum terrain clearance altitude must be recorded.

NOTE 2: Cruise operations are considered to exist beyond the airport control area until inside the destination airport control area for VFR operations. Distances may extend to 10 NM from the airport (takeoff and landing) for IFR operations. Use of the nearest runway logic is permissible provided suitable logic is incorporated to ensure that the transitions to the terminal logic will typically occur only when the airplane is in terminal airspace.

NOTE 3: The values shown in column E may be reduced by 50 feet (to permit a level off to occur at 150 feet above the obstacle) provided that it can be demonstrated that the basic TAWS Mode 1 alert (sink rate) is issued at, or above, the altitude specified in column E for typical terrain topographies.

NOTE 4: The values shown in Column F are appropriate for an airplane without an Autopilot or Flight Director function, and are based upon 10-15 percent of the vertical velocity, which is appropriate to manual flight and small general aviation airplane operations.

**APPENDIX 4. FEDERAL AVIATION ADMINISTRATION MINIMUM
PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND
WARNING SYSTEM FOR CLASS C (continued)**

TABLE A

Enroute Descent Alerting Criteria

Alerting for Premature Descent during Cruise
ABCDEF

VERT	
SPEED	
(FPM)ALT LOST	
WITH 3 SEC	
PILOT	
DELAYALT	
REQ'D TO	
L/O WITH	
1 G PULLUPTOTAL ALT	
LOST DUE TO	
RECOVERY	
MANEUVERMINIMUM	
TAWS WARNING ALERT HEIGHT	
(ABOVE	
TERRAIN)MAXIMUM	
CAUTION	
ALERT HEIGHT	
(ABOVE TERRAIN)	
50025126226 550	
100050454254 600	
200010017117317 800	

TSO Note: Paragraph 1.3 in the TSO is changed to specify altitude levels, test speeds and pull-ups more appropriate to small aircraft:

1.3 Cruise Level Flight Requirement. During level flight operations (vertical speed is ± 200 feet per minute), a terrain alert should be posted when the airplane is within 250 feet of the terrain and is predicted to be equal to or less than 200 feet within the prescribed test criteria. See Table B for Test Criteria.

NOTE 1: The actual values for the airplane altitude, distance and time from the terrain cell when caution and warning alerts are posted must be recorded.

APPENDIX 4. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASS C (continued)

TABLE B

Level Cruise Flight Alerting Criteria	
GROUND SPEED	
(KT)	HEIGHT OF TERRAIN CELL (MSL)
	TEST RUN
	ALTITUDE
	(MSL)
	ALERT
	CRITERIA
100	5000
5340	(+0/-50)
	No alert
150	5000
5340	(+0/-50)
	No alert
200	5000
5340	(+0/-50)
	No alert
100	5000
5240	(+0/-50)
	Must alert
150	5000
5240	(+0/-50)
	Must alert
200	5000
5240	(+0/-50)
	Must alert

1.4 Terminal Area (Intermediate Segment) Descent Requirement. Not applicable.

1.5 Terminal Area (Intermediate Segment) Level Flight Requirement. Not applicable.

1.6 Final Approach Descent Requirements. Revised to specify altitude levels, test speeds and pull-ups more appropriate to small aircraft:

- a.** See Table E. Column A represents the test condition. Columns B, C, and D are for information purposes only. Column E represents the Minimum Altitude for which TAWS alerts must be posted to perform their intended function. Column F represents the Maximum altitude for which TAWS alerts may be provided in order to meet the nuisance alert criteria. See appendix 3, section 4.0.
- b.** For each of the Descent rates specified below, recovery to level flight at or above 100 feet terrain clearance is required.

APPENDIX 4. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASS C (continued)

c. Test Conditions for 1.6:

Assumed Pilot response time:	1.0 seconds minimum
Assumed constant G pull-up:	1.0 g
Minimum Allowed Terrain Clearance:	100 feet AGL
Descent rates:	500, 750, and 1000 fpm

Assumed Pilot Task for Column F: Level off at 250 feet above the terrain per Appendix 4, Table 3-1 Required Obstacle Clearance (ROC).

NOTE 1: The actual values for the airplane altitude, distance and time from the terrain cell when caution and warning alerts are posted and the minimum terrain clearance altitude must be recorded.

NOTE 2: The values shown in Column F are appropriate for an airplane without an Autopilot or Flight Director function, and are based upon 10 percent of the vertical velocity that is appropriate to manual flight and small general aviation airplane operations.

TABLE E

Approach Descent Alerting Criteria
ABCDEF

VERT	
SPEED	
(FPM)ALT LOST	
WITH 1 SEC	
PILOT	
DELAYALT	
REQ'D TO	
L/O WITH	
1 G PULLUPTOTAL ALT	
LOST DUE TO	
RECOVERY	
MANEUVERMINIMUM	
TAWS WARNING ALERT HEIGHT	
(ABOVE	
TERRAIN)MAXIMUM	
CAUTION	
ALERT HEIGHT	
(ABOVE TERRAIN)	
500819109 300	
75012214114 325	
100017421121 350	

APPENDIX 4. FEDERAL AVIATION ADMINISTRATION MINIMUM PERFORMANCE STANDARD (MPS) FOR A TERRAIN AWARENESS AND WARNING SYSTEM FOR CLASS C (continued)

1.7 Landing Flight Requirement. Applies as written.

2.0 through 2.2. Forward Looking Terrain Avoidance Imminent Impact Test Conditions. Apply using Table G for speed cases of 100 through 250 knots, however change the incremental pull from 0.25g to 1.0g in Note 2.

3.0 and 3.1 Premature Descent Alert Test Conditions. Apply as written.

4.0 Nuisance Alert Test Conditions - General. Apply as written.

4.1 4000 FPM. Not applicable.

4.2 2000 FPM. It must be possible to descend at 2000 FPM and level off 500 feet above the terrain using a normal level off procedure (leading the level off by 10 percent of the vertical speed), without a caution or warning alert.

4.3 1000 FPM. It must be possible to descend at 1000 FPM in the Final Approach Segment and level off at 250 feet using the normal level off procedure described in 4.2 above, without a caution or warning alert.

5.0 Nuisance Test Conditions for Horizontal and Vertical Flight Technical Errors. Applicable as written.

5.1 Test Cases. Is applicable as written however, test cases are limited to locations 3, 6, 7, and 8 in **Table I**.

6.0 Test Conditions Using Known Accident Cases. Paragraphs 6.0 through 6.3 are to be determined by the applicant using actual NTSB GA accidents. Since detailed data is usually not available, reasonable constructed scenarios matching the actual known accident data may be demonstrated. Pulls of up to 1.0g may be used instead of the 0.25g as specified in **6.2**, computation and Recording.

7.0 Class C Equipment Test Requirements for Excessive Descent Rate. Apply Class B as written.

8.0 Class C Equipment Test Requirements for Negative Climb Rate or Altitude Loss After Takeoff. Apply Class B as written.

9.0 Class C Equipment Test Requirements for the Altitude Callouts. Apply Class B as written.